



Movie 5.1 System

It saves on space, not on audio quality!

Don't be fooled by the compact size of the Movie 5.1 System. It is not just recommended for young audio enthusiasts or home cinema beginners. This package of three K50 front speakers, two K40 surround speakers and one V8 subwoofer has been curated by M&K engineers to play back multi-channel movie soundtracks and games with both intense dynamics and immense scale. The Movie 5.1 System is capable of conveying everything from the quietest atmospheric vignettes to the loudest fast-paced action scenes. All the while, against competing music and sound effects, the K50 front center speaker is capable of delivering crystal clear dialogue every time.

With a slim depth of only 85 mm, the K50 front speakers can be easily mounted on the wall. Together with the K40T Tripole surround speakers and the V8 Movie active subwoofer, the six components form a powerful home cinema setup for your living room or office.

The Movie 5.1 System is sold as a complete set and delivered in one box consisting of the following:

- 3 x K50 speakers
- 2 x K40T Tripole® speakers
- 1 x V8 Movie subwoofer
- Wall brackets

K50

Nominal system impedance: 4 ohm (Z-min 4.9 ohm)
Frequency Response: 100-20Khz (average response in room +/- 2dB)
Frequency Roll Off: 100Hz (-6dB 100 Hz near field wall mounted)
Crossover Frequency: 1.8 Khz "Phase focused" (4th&2nd order)
Tweeter (shielded): 1" Dome – Coated silk dome / Neodymium magnet
Woofer (shielded): 4" Coated glass fibre
Power Handling: 80 watt Long term IEC-268-5 (cycled input 100-20Khz)
Power Handling: 50 watt (Rated IEC-268-5 (constant input 100-20Khz)
Recommended Amplifier Power: 25-125 watt
Sensitivity: 85 dB (Average SPL 2.83 Volt / 1mtr (on axis 200-10KHz)
System Princip: Sealed enclosure
Connection: Terminal gold plating (Screw for 5 mm cable / Banana)
Dimensions HxWxD: 9.8 x 5.1 x 3.3" - 25 x 13 x 8,5cm (incl grill)
Weight: 4.4 lb / 2.0 kg
Finish: Black vinyl

K40T

Nominal system impedance: 4 ohm (Z-min 4.6 ohm)
Frequency Response: 100-20Khz (average response in room +/- 2dB)
Frequency Roll Off: 100Hz (-6dB 100 Hz near field wall mounted)
Crossover Frequency: 2.0 Khz "Phase focused" (4th&2nd order)
Tweeter (shielded): 1" Dome – Coated silk dome / Neodymium magnet
Woofer (shielded): 4" Coated glass fibre
Side drivers (shielded): 2 X 3" (Polymer Coated Textured Paper)
Power Handling: 80 watt Long term IEC-268-5 (cycled input 100-20Khz)
Power Handling: 50 watt (Rated IEC-268-5 (constant input 100-20Khz)
Recommended Amplifier Power: 25-125 watt
Sensitivity: 85 dB (Average SPL 2.83 Volt / 1mtr (on axis 200-10KHz)
System Princip: Sealed enclosure
Connection: Terminal gold plating (Screw for 5 mm cable / Banana)
Dimensions HxWxD: 7.7 x 7.8 x 4.8" -19.5 x 20 x 12,2 cm (incl grill)
Weight: 6.5 lb / 2.9 kg
Finish: Black vinyl

V8 Movie

Amplifier power 150 watt RMS /250 watt peak
Frequency response 30-200Hz +/- 2dB
Total harmonic distortion >0.5% 150 watt, 4 ohm
AC power consumption Standby/Average/Max 0,5/30/150W
AC Line Voltage 100-240 VAC 50/60Hz 3,15A
LFE Input L/R line level RCA
LFE Passthrough output. L/R line level RCA
Low pass filter 60–200 Hz Continuously variable
Phase 0-180 deg : Continuously variable
Volume Continuously variable
Dimensions HxWxD 13.3 x 10.3 x 11.4" / 337 x 260 x 290 mm
Weight 24,3 lbs / 11,0 kg
Finish Black vinyl

